



DECLARATION OF PERFORMANCE

No. GP1

1. Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product.

Dry-pressed ceramic tiles, with water absorption $E \leq 0,5 \%$

2. Intended use(s)

For floors and walls, interior and exterior

3. Name or registered trade mark, and contact address of the manufacturer
Grespania, S.A., CV-16, Km. 2,200, 12006, Castellón (España)

4. System(s) of assessment and verification of constancy of performance (AVCP)
System 4

5. Name and identification number of notified laboratory, if relevant
Task carried out / AVCP system / Document issued an date of issue
Not apply

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL} /A1	EN 14411 :2012
Release of dangerous substance: - Cadmium - Lead	N.P.D. N.P.D.	
Breaking strength	> 1300 N	
Slipperness	N.P.D..	
Adhesion for cementitious adhesive, type C2	>1,0 N/mm2	
Thermal shock resistance	Passed	
Durability for : - interior use - exterior use: freeze / thaw cycle	Passed Passed	
Tactility	N.P.D.	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and behalf of the manufacturer:

Name: Máximo Dolz

Function: Technical Manager

GRESPANIA, S.A.
Ctra. Castellón-Alcora CV-16 Km. 2,200
12006 CASTELLON (ESPAÑA)

Castellón, 01-07-2013

Signature: